

APR-26-2005 10:22
Application No.: 10/733,687
Rule 312 Amendment dated April 26, 2005
Attorney Docket No.: 3436-014 CON

Listing of Claims:

This listing of claims will replace all prior versions and listings of claims in the subject application:

1. (ORIGINAL) A method of operating a wind power installation comprising an electric generator drivable by a rotor for supplying electrical power to an electrical network (6), in particular its connected consumers (8), characterised in that the power supplied to the network (6) by the generator is regulated in dependence on an electrical voltage applied to the network (6).

Claims 2-8. (PREVIOUSLY CANCELED)

9. (PREVIOUSLY ADDED) A method of operating a wind power installation including an electrical generator driven by a rotor for supplying electrical power to an electrical network having a network voltage and being connected to a customer, comprising:

sensing said network voltage;

supplying electrical power to the electrical network at a supplied power level in accordance with said network voltage; and

adjusting said supplied power level in accordance with said network voltage.

10. (PREVIOUSLY ADDED) The method of claim 9 further comprising increasing said power level as said network voltage increases from a level U_{\min} to a level U_3 .

11. (PREVIOUSLY ADDED) The method of claim 10 wherein said step of adjusting includes reducing said power level to a lower level when said network voltage exceeds a threshold value U_1 .

12. (PREVIOUSLY ADDED) The method of claim 10 further comprising increasing said power level linearly between said levels U_{min} and U_3 .

13. (PREVIOUSLY ADDED) The method of claim 12 wherein said power level is zero for network voltages below U_{min} .

14. (PREVIOUSLY ADDED) The method of claim 13 further comprising maintaining said power level constant while the network voltage is between U_3 and a level U_1 , U_1 being larger than U_3 .

15. (PREVIOUSLY ADDED) The method of claim 10 further comprising maintaining said power level constant while the network voltage is between U_3 and a level U_1 , U_1 being larger than U_3 .

16. (PREVIOUSLY ADDED) The method of claim 9 wherein said generator is capable of generating said electrical power at a nominal power level dependant on current wind conditions, wherein said lower level is lower than said nominal power level.

17. (PREVIOUSLY ADDED) The method of claim 9 wherein said sensing includes sensing said network voltage at the point at which said electrical power is fed to said electrical network.

18. (PREVIOUSLY ADDED) The method of claim 9 further generating said electrical power at a predeterminable frequency.

19. (PREVIOUSLY ADDED) The method of claim 18 wherein said electrical network is operating at a network frequency, wherein predeterminable frequency corresponds substantially to said network frequency.

20. (PREVIOUSLY ADDED) A wind power installation for delivering electrical power to an electrical network comprising:

a rotor rotated by wind;

an electrical generator coupled to said rotor and adapted to supply electrical power at a supplied power level to the electrical network; and

a regulating device having a voltage sensor for sensing a network voltage associated with the electrical network, said regulating device being coupled to said electrical generator to control said power level in accordance with said network voltage, wherein said regulating device is adapted to adjust said supplied power level in response to variations of said network voltage.

21. (PREVIOUSLY ADDED) The apparatus of claim 20 wherein said regulating device generates a control signal responsive to the increase of said network voltage from a level U_{mh}

to a level U3, said control signal increasing said supplied power level from a level P2 to a level P1.

22. (PREVIOUSLY ADDED) The wind power installation of claim 21 wherein said control signal increases said supplied power levels linearly between P2 and P1.

23. (PREVIOUSLY ADDED) The wind power installation of claim 22 wherein said power level P2 is zero.

24. (CURRENTLY AMENDED) The wind power installation of claim 21 wherein said regulating device generates another control signal responsive to the increase of said network voltage from a level U3 to a level U_2 U1, said another control signal maintaining said supplied power level at level P1.

25. (PREVIOUSLY ADDED) The wind power installation of claim 24 wherein said regulating device generates a third control signal responsive to the increase of said network voltage from a level U3 to a level U_{max} , said third control signal decreasing said supplied power level from level P1 to level P2.

26. (PREVIOUSLY ADDED) The wind power installation as set forth in claim 25 wherein said regulating device is adapted to reduce said supplied power level from said level P1 to said level P2 linearly.

27. (PREVIOUSLY ADDED) The wind power installation as set forth in claim 20 wherein said regulating device has a microprocessor.

28. (PREVIOUSLY ADDED) A method of operating an energy-generating apparatus including an electric generator for supplying electrical power to an electrical network, the electrical network being connected to at least one consumer and having a network voltage that fluctuates with demand, said method comprising:

supplying electrical power from said electrical generator to said electrical network at a supplied power level; and

regulating said supplied power level by increasing said supplied power level from a level P2 when said network voltage exceeds a value U_{min}

29. (PREVIOUSLY ADDED) The method as set forth in claim 28 wherein said supplied power level is regulated by increasing said supplied power level to a level P1 as said network voltage increases from said value U_{min} to a level U3.

30. (PREVIOUSLY ADDED) The method as set forth in claim 29 wherein said supplied power level is increased linearly.

31. (PREVIOUSLY ADDED) The method as set forth in claim 29 wherein said supplied power level is maintained at level P1 as set network voltage increases above said value U3.

32. (PREVIOUSLY ADDED) The method as set forth in claim 29 wherein supplied power level P2 is zero.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.